



# Compact Scales

*Models CS200, CS2000 and CS5000*



Ohaus Compact Scales are ideal when cost matters and dependable results are a must. These uniquely designed scales have a wide variety of applications, more than any other scale in their class. The three portable models range in capacities from 200g to 5000g, and are perfect for use in light production, in the field, the kitchen, the office, and more. Easy operation, long battery life, and great performance make Compact Scales a truly remarkable value.

- Sleek, low profile design
- Large high contrast display
- Energy-saving auto shut-off feature
- Battery or AC powered
- Rugged plastic construction

# Compact Scales Models CS200, CS2000 and CS5000

## Specifications

| Item Number                   | CS200   | CS2000 / CS2000P <sup>†</sup> | CS5000 / CS5000P <sup>†</sup> |
|-------------------------------|---|-------------------------------|-------------------------------|
| Capacity x Readability (g)    | 200 g x 0.1 g   | 2000 g x 1.0 g                | 5000 g x 2.0 g                |
| (oz)                          | 7.05 oz x 0.01 oz   | 4lb:6.55 oz x 0.05 oz         | 11lb:0.4 oz x 0.1 oz          |
| Repeatability (Std. dev.) (g) | 0.1   | 1.0                           | 2.0                           |
| Linearity (g)                 | ±0.1  | ±1.0                          | ±2.0                          |
| Weighing units                | g, lb:oz  |                               |                               |
| Zero range                    | to capacity by subtraction                                |                               |                               |
| Stabilization time            | 3 seconds   |                               |                               |
| Optimum operating temp.       | 64°-77°F / 18°-25°C                                       |                               |                               |
| Power requirements            | 3-AA alkaline batteries (included) or optional AC adapter |                               |                               |
| Calibration                   | user calibration from keypad                              |                               |                               |
| Auto shut-off                 | 5 minutes no activity (battery operation only)            |                               |                               |
| Display (in/mm)               | LCD (0.4 / 11)  |                               |                               |
| Pan size L x W (in/cm)        | 5.75 x 5.25 / 14.5 x 13.3                                 |                               |                               |
| Dimensions L x W x H (in/cm)  | 8.0 x 5.5 x 1.5 / 20.3 x 14.0 x 3.8                       |                               |                               |
| Net Weight (lb/kg)            | .91 / .47   |                               |                               |

<sup>†</sup> U.S. Postal chart included

## Standard Feature s


Low battery indicator, overload and underload indicators, auto shut-off, rugged plastic construction, tactile feedback keypad.

## Optional Accessories

1050 ml capacity bowl, AC adapter, stainless steel pan cover, calibration masses, U.S. Postal chart

## Industry Leading Quality and Support

All Ohaus Compact Scales are manufactured under an ISO 9001:2000 Registered Quality Management System. Our rugged construction and stringent quality control have been hallmarks of all Ohaus products for nearly a century.



LUS08-99 REV05-01 © Copyright Ohaus Corporation

### Ohaus Corporation

\* 19A Chapin Road  
P.O. Box 2033  
Pine Brook, NJ 07058 USA

Tel: 800.672.7722  
973.377.9000  
Fax: 973.593.0359

[www.ohaus.com](http://www.ohaus.com)

*With offices throughout Europe,  
Asia, and Latin America*

\* **ISO 9001: 2000**  
Registered Quality Management System

