

MCW

MCW "PROFESSIONAL" SERIES CRANE SCALES



MCW...R2

Reliable and easy to use AISI 304 stainless steel crane scales suitable for indoor and outdoor use, for industrial weighing applications. Reduced lifting distance of the crane. IP67 protection from dust and rain. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights.

MAIN FEATURES

- Large backlit 25mm LCD display easily visible in all lighting conditions and also with low temperatures.
- Fitted with standard approved upper galvanized shackle and standard approved bottom swivelling hook.
- Reduced distance between the upper shackle and bottom hook.
- Precision: +/- 0.05% F.S.
- Waterproof keyboard with 5 keys: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- MODE-key configurable as:
PEAK (maximum value read), HOLD (blocking the weight viewed), Weighs accumulation, lb/kg/N conversion.
See the user manual for the list of the functions.
- IP67 stainless steel case (dust and rain).
- Fitted with remote control for up to a 8 m distance. The remote control may be configured by the customer as automatic tare only, or as a remote keypad.
- Rechargeable sealed battery with a 40-hour life battery. On request, it is available a second battery for a 24/7 use.
- Equipped with 230Vac 50 Hz battery charger.
- Operating temperature: -10 /+40 °C.
- Programmable digital filter and auto switch-off.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Attached thermal printer option box or virtual and integrated printer.
- Integrated thermal printer (code TPRPR2 only for the "R2").
- WI-FI interface.
- RF weight transmission to remote indicator up to over 70m indoors, 150m outdoors, adequate environmental and installation conditions.
- 433MHz radiofrequency remote control (compatible with remote indicator).
- DOT red LED display of 40mm.
- Second battery for a 24/7 use (code MCWKBK for "R2" models; code MCWBK for MCW3000, MCW3000M, MCWT6, MCWT6M models).
- ACCREDIA calibration certificate according to OIML/ASTM standards.
- Remote weight indicator (see DFW..., 3590..., TRS..., DGT60.. Series' indicators) with printer connected through radio frequency.

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- Infrared 19-key remote control (standard), operating up to 8m:
zero; tare / manual tare; enable / disable function; print; switch-off.
- Radiofrequency 6-key remote control (optional) operating up to 50m:
zero; tare; enable / disable function; print; switch-off.

VERSIONS

MCW Crane scales: Available versions

Code	Max (kg)	d (kg)	d* HR (kg)	CE-M 3000e (kg)
MCW300R2	300	0,1	0,05	
MCW600R2	600	0,2	0,1	
MCW1500R2	1500	0,5	0,2	
MCW3000	3000	1	0,5	
MCWT6	6500	2	1	
MCW150MR2 M	150			0,05
MCW300MR2 M	300			0,1
MCW600MR2 M	600			0,2
MCW1500MR2 M	1500			0,5
MCW3000M M	3000			1
MCWT6M M	6000			2

(*) The HR division is obtainable only with the relative EHR option



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE