

IPWI

TPWI SERIES PALLET TRUCK SCALE



High performance stainless steel pallet truck scales with built-in multirange electronic weighing. The four IP68 stainless steel load cell weight detection guarantees the best accuracy in all work conditions. Reliable and suitable for one who needs to weigh accurately any type of product on a pallet.
Available also CE-M APPROVED

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Fork dimensions 1182 x 550 x 80 mm.
- Weighs about 135 kg.
- Bearing structure entirely in extra thick STAINLESS steel.
- Lifting pump in STAINLESS steel.
- Vulkollan steering wheels and double loading rollers.
- 4 IP68 stainless steel shear beam load cells.
- Weight indicator with waterproof IP68 STAINLESS STEEL case, easy to clean and resistant to harsh and corrosive environments; large 25mm high contrast LCD display, clearly visible also in poor lighting conditions, and membrane waterproof keypad, with 17 numerical/functional keys.
- Calibration and Set-Up configurable from keyboard or from PC with DINITOOLS.
- Power supply through built-in rechargeable battery.
- 50-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low Battery Warning.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control

MAIN FUNCTIONS


- Zeroing, Tare, Printing, numeric IDs
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Accumulation
- Formula weighing
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions)
- Hold and Peak
- Set Point Control (with optional interface)

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Thermal printer / Modem radio option box
- WI-FI interface
- Alibi memory with time-date
- Time-Date
- 2 inputs + 2 outputs configurable on gross or net weight
- 680 mm fork width (ask for price estimate)
- Special fork length from 850 to 1500 mm (ask for price estimate)
- Special capacity and/or division (ask for price estimate)
- Special wheels available with price estimate

VERSIONS

Available versions

Code	Max (kg)	d (kg)	CE-M 3000e (kg)
TPW20I	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPW20IM 	1000 / 2000	--	0,5 / 1



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE